



3D Model Available

Regulators are shipped with a flush-out plug for maintenance only. Installing this plug will force the regulator open so that material flows freely through. While installed, **outlet pressure will be equal to supply pressure**. This is used to flush debris from the regulator.

GPR5000-3000-1250:

Material pressure regulator has maximum primary pressure of 3,000 psi and controlled secondary pressure between 400 and 1250 psi. Inlet and outlet ports are 3/8 NPT. Includes mounting bracket for easy panel mounting. Also includes a 0-2,000 PSI output pressure gauge.

SALES DRAWING			GP REEVES INC HOLLAND, MI USA	
UNLESS SPECIFIED: DIMENSIONS IN INCHES			DESCRIPTION: GREASE PRESSURE REGULATOR	
<small>PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF G.P. REEVES INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF G.P. REEVES INC. IS PROHIBITED.</small>				
MODELED	BY	DATE	DRAWING NO.	SHEET 1 OF 2
ACL	ACL	12/21/23	GPR5000-3000-1250	REV A
DETAILED	ACL	12/21/23	WEIGHT:	SIZE A SCALE: 1:3

Last updated: 1/10/2024